





中空旋转平台技术参数
Technical Parameters of Planetary Reducer

旋转平台轴承 Rotating Platform Bearing	交叉滚子轴承 Crossed Roller Bearing					容许输出转速 Permissible Output Speed	300rpm	安装方式 Mounting Position	任意角度 Arbitrary Angle
旋转位置 Rotational Position	360° (任意角度旋转) 360° (Rotation at any Angle)					定位精度 Positioning Accuracy	≤1arcmin	润滑 Lubrication	长效润滑 Long-lasting Lubrication
匹配电机 (尺寸) Matching Motor (Size)	松下 400W ø14-ø50-ø70-M4 Panasonic 400W ø14-ø50-ø70-M4					重复定位精度 Repetitive Positioning Accuracy	±6arcsec	使用环境温度 Operating Temperature	-20℃~90℃
速比 Reduction Ratio	1:20	1:30	1:40	1:50	-	容许轴向负载 Allowable Axial Load	1000N	使用寿命 Service Life	20000h (间歇运转) (Intermittent Operation)
容许转矩 Allowable Torque	26N.m					容许径向负载 Allowable Radial Load	500N	噪音值 Level of Noise	≤62dB
容许惯性力矩 Allowable Moment of Inertia	39N.m					工作台面平行度 Parallelism of Output Platform	0.02mm	光电开关 Level of Noise	672/674
转动惯量 Rotational Inertia	1375.29*10 ⁻⁶ kg.m ²					工作台面跳动 Runout of Output Platform Surface	0.01mm	防护等级 Level of Production	IP65
订货型号规格 Order Model Number and Specifications	SRG110ZM-(速比)K-400P (14-50-70-M4)					工作台面跳动 Runout of Output Platform Excircle	0.01mm		



中空旋转平台 Hollow Rotating Platform				型号 Model:
				SRG110ZM-(速比)K-400P
幅面 Size				规格 Specifications:
				14-50-70-M4
单位 Units	重量 Weight	比例 Scale	投影方式 Projective Mode:	
A3	mm			